



# CIR-P37X56

## Main Feature

- \* SAMSUNG Chipset
- \* 37X Optical & 16X Digital Zoom,
- \* Color 560TVL, Black 680TVL,
- \* ATR, ICR
- \* IR-III : 120-150M
- \* Pan range: 0°~360° Continue (Not 355° )
- \* Tilt range: 0°~90° Flip
- \* Pan Speed: Max 300°/sec Preset: 128
- \* Weatherproof Outdoor IP66



Power supply	DC12V 5A
Power consumption	60W
Sync system	Internal selectable
Preset	128 presets
Auto tour	6
Pattern	120s
Alarm	4 channels input & 1 channel output
Privacy masking	8 (some model only)
Zoom-rotation Interaction	Control speed auto adjust according to the focus length
Auto flip	Rotate 180 when camera tilts to the vertical position
Auto pan scan	360°Programmable
Pan speed	0° -- 120°/s
Pan rotation range	360°continues
Title range	Tilt 90°
Tilt speed	0° -- 55°/s
Control mode	RS485
Baud Rate	2400/4800/9600/19200 bps
Fan & heater	Fan & heater auto-start (only outdoor dome)
Relative humidity	10-75% (incoherence situation)
Environment temp	Indoor dome : 0°C — +40°C
	Outdoor dome : -35°C -- +55°C