Hubei Jucro Electric CO., LTD.

ADD: 5-1-2103, No.169-5, Tiyuchang North Rd., 443000, Yichang, Hubei, P.R.CHINA. Website: www.jucro.com Email: qiumin@jucro.com

1. General

HVJ5-1.14/250 AC vacuum contactor is designed for long-distance making and breaking of circuit, frequent starting and controlling of AC motors in the power systems, with AC 50Hz-60Hz, rated voltage of 1,140V and rated current to 250A. It also can be equipped with thermal relay and all kinds of protection apparatus like electromagnetic starter, especially applied to explosion-proof starter and so on.

2. Main technical parameter

Product model	Rated voltage (V)		D-4-14	Main contacts parameters			Power frequency voltage		
	Main circuit	Control circuit	Rated current (Main circuit) A	Opening	Over	Final	resistance V(effective value)		
				distance	travel	pressure	Main	Auxiliary	Control
				(mm)	(mm)	(N)	circuit	circuit	circuit
HVJ5-1.14/250	1140	36.110.220.380	250	2±0.2	1±0.2	30±3	4200	2500	2000

Product model	Making capacity	Breaking capacity	Limit breaking	Electricity life times		Mechanical life times	Overload capacity
	Capacity	сарасіту	current(A)	AC3	AC4	ine times	capacity
HVJ5-1.14/250	10Ie,100times	8Ie,25 times	4500,3 times	60*10 ⁴	6*10 ⁴	300*10 ⁴	8Ie 10S

Remark: "Ie" is Rated current of main circuit.