

Hubei Jucro Electric CO., LTD.

ADD: 5-1-2103, No.169-5, Tiychang North Rd., 443000, Yichang, Hubei, P.R.CHINA.

Website: www.jucro.com

Email: qiumin@jucro.com

HVJ30-1.14/1000、1250 series AC vacuum contactor is applicable for AC 50HZ power system of rated voltage 1.14KV and rated current up to 1000 A ~ 1250A to open and close circuit, start and control AC motor frequently. It is suitable for composed magnetic starter with various protective devices (JDB electronic integrated protector, JR9 type over current protection device, resistance-capacitance absorbers). It is particularly suitable for compose a explosion-proof magnetic starter and large mineral switchgear.

Type	Unit	HVJ30-1.14/1000	HVJ30-1.14/1250
Rated voltage	KV	1.14	1.14
Rated current	A	1000	1250
Making capacity	A	5000 (100 times)	
Breaking capacity	A	4500 (10 times)	
Limit breaking capacity	A	5000 (3 times)	
Electrical life times(AC3)	times	600,000	
Electrical life times(AC4)	times	6,000	
Mechanical life times	times	1,000,000	
Rated operating frequency (AC3)	times /h	600	
Rated operating frequency (AC4)	times /h	120	
Short-time operating frequency (20s)	times /h	1000	
Contacts separation	mm	2.8±0.1	
Over travel	mm	1.0±0.1	